

ATTACK6PEOM-BSC

FIREFIGHTERS RANGE

Leather-Textile FIRE PROTECTION

- Structural fires
- Fire-fighting interventions
- Training compartments



CIVIL SAFETY Label

«Certification after washing ensures that all EN659 values are the same before and after 10 washes»



AET : 0072/011/162/05/19/0199 (IFTH)

STANDARDS (DETAILS ON WEB SITE)
www.rostaing.com/normes-securite

SIZES



COMPOSITION

Palm Washable water-repellent goat leather
Back AIRSYSTEM® fabric
Lining UNDERTECH®+ aramid felt on the palms
Cuff Heat treated split leather
Total length 40 cm
Hanging system Right glove: carabiner
 Left glove: ½ ring

CARE



PACKAGING

Bag of 1 pair / Box of 20 pairs



Radiating heat resistance
Technology

AIRSYSTEM®
ROSTAING®
diamond-shaped honeycomb



PROTECTION FROM THERMAL BRIDGES



Heat resistance 350°C
Water and oil resistant
flexible leather

Technical lining

UNDERTECH®
ROSTAING®

Optimum heat and cutting resistance

Porelle® Membrane

Waterproof, flame, chemical and bacteria resistant



Reinforcement zone

Radiant heat



Vein-patch



Tightening strap

Carabiner and hanging dice

Glove size

Traceability label:



CERTIFIED AFTER 10 WASHES