

High resistance to small splashes of molten metal and sparks



Enhanced fit on the wrist through tightening rubber on the back

Heat-resistant (250°C) cow split leather cuff for extended protection.  
Total length : 39cm



Cow split leather, tanned in France, heat resistant (250°C)

Para-aramid/PE lining for maximum cut protection 5/5 to EN388

Certified according to welder standard EN12477 (A-2005)



## NORMS :

### EN 388



4543

|                          |            |
|--------------------------|------------|
| Abrasion resistance :    | 4/4 levels |
| Blade cut resistance :   | 5/5 levels |
| Tear resistance :        | 4/4 levels |
| Perforation resistance : | 3/4 levels |

EN 12477  
+  
A1 (2005)

Protection for  
A type welder

### EN 407



413244

|                                |     |
|--------------------------------|-----|
| Fire resistance                | 4/4 |
| Contact heat                   | 1/4 |
| Convective heat                | 3/4 |
| Radiant heat                   | 2/4 |
| Small molten metal projections | 4/4 |
| Large molten metal projections | 4/4 |

8 to 11

## APPLICATIONS :

- Hand climp welding

## PERFORMANCE :

Homologation delivered by the notified body CTC/LYON  
N° 0072/011/162/11/13/1171

Cleaning :



Packaging :

Box of 20 pairs

